Digital dial indicators

Digital dial indicators with digital and digital-analog read-out.

- Measuring range: 0 - 12.5 mm.
- Resolution: 0.002 or 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Automatic switch-off.
- Reset/preset.
- Clamping stem: ø 8 mm.
- Dial diameter: 62 mm.
- Dial 360° rotatable.
- Reversible measuring direction.
- With determination of the reversal point.
- Adjustable tolerance limits.
- Power supply: 1 battery type CR2032.



909.251

PRICE

Item No.	Measuring range/mm	Resolution mm	Accuracy mm	Measuring force/N	Price HUF
909.250	0 - 12.5	0.002	±0.015	1.8 - 3.0	
909.251	0 - 12.5	0.001	±0.006	2.2 - 3.5	

Option:
495.157 Spare battery

Digital dial indicators

Universal digital indicators with both digital and digital-analog display of the measuring value, and can also be rotated over 340° to ensure easy read-out in all positions.

- Measuring range: 0 - 12.7 mm.
- Resolution: 0.001 mm.
- Analog resolution: 0.001 / 0.002 / 0.01 / 0.02 / 0.05 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Automatic switch-off.
- Reset/preset.
- Clamping stem: ø 8 mm.
- Dial diameter: 61 mm.
- Dial 340° rotatable.
- Reversible measuring direction.
- Adjustable tolerance limits.
- Protection: IP54.
- Power supply: 1 battery type CR2032.



907.879

PRICE

Item No.	Measuring range/mm	Accuracy mm	Price HUF
907.879	0 - 12.7	±0.01	
907.878	0 - 12.7	±0.005	

Option:
495.157 Spare battery

C05.320 HOD.20200430